

COMPACT CSL (CARTON SECURITY LABELLER)

DESCRIPTION

Capable of increasing the Tamper Evident hand labelling of small cartons by at least 3 times, the CSL (Carton Security Labeler) is manually operated by swiping the carton over the top plate, a white nylon guide provides positioning of the carton, the label is fed out electrically, when the carton comes in contact with the application roller the label is applied to the front face of the carton and the underside, while the backing paper is being rolled up automatically.



FEATURE LIST

- Rewinds backing paper - preventing slip and fire hazard
- Low voltage design - providing safety during operation
- Designed for continuous trouble free operation
- Eliminate RSI Risk
- Mechanical starwheel label sensor - for positive label sensing of paper or clear labels
- Single motion label placement - for speed and efficiency
- Accepts a wide range of carton sizes - see capacity below
- Increase manual labelling productivity by 3 times
- One second cycle time - per label (double ended cartons in 3 seconds)
- Improve labelling quality
- Minimise label waste
- Industrially robust - Food Grade - Stainless Steel construction
- Suitable for clear or opaque Die-Cut labels
- Tool-less operation & adjustment
- Simple to operate – almost no skill or training is required to obtain an excellent result
- Quick to set up – within a couple of minutes a new job can be set up and running, increasing productivity immediately
- Portable - weighing 8kg the CSL can be moved easily

NOTES:

Compact Labelling Systems - Australia
Matthews Australasia Pty Ltd.
35 Laser Drive, Rowville, Vic. 3178 Australia
Tel. 1300 263 464 (24 hours)
E-mail: info@matthews.com.au
<http://www.compactlabelling.com.au>

COMPACT CSL (CARTON SECURITY LABELLER)

TECHNICAL DATA

SPECIFICATIONS

Overall Dimensions	L570xW160xH260mm
Power Requirements	240V
Weight	8kg

CAPACITY

Min' Label Size	10mm W x 20mm L
Max' Label Size	30mm W x 40mm L
Min' Roll Diameter	39mm
Max' Roll Diameter	250mm
Gap between labels	3mm
Carton Widths	40mm to 140mm

NEW STANDARD

- Label Roll Bracket - capable of holding a 250mm diameter label roll.

NOTES: